



FEATURES



- Wireless digital transmission of Video and Audio
- Free Input Voltage (DC 11V ~ 32V)
- Motorized shutter camera support & camera heater support
- Remote controlled pairing
- Re-pair function to enable interchanging trailers
- Signal strength indicator
- Status LEDs
- High quality thermoplastic urethane cables (TPU)
- IP69K waterproof (transmitter & receiver)
- Anodized aluminum housing (corrosion-proof)

Specifications

General	Operating frequency	2400MHZ-2483MHZ
	Modulation system	FSK
	Signal reception area	150-200M (in open air)
	Operating temperature	-30°C ~ 80°C
	IP Rating	IP69K
Transmitter (TX)	Power supply	DC 11 ~ 32V
	Power consumption	Max. 1.87 W (at DC 11V)
	Video input	CVBS 1.0VP-P, 75Ω
	Audio input	AUDIO MAX 2VP-P, 50Ω
	TPU cable length	Approx. 400cm
	Dimensions	131mm x 100mm x 25.6mm
	Weight	0.28KG
Receiver (RX)	Power supply	DC 11 ~ 32V
	Power consumption	Max. 1.87 W (at DC 11V)
	Video output	CVBS 1.0VP-P, 75Ω
	Audio output	AUDIO MAX 2VP-P, 50Ω
	Pixels	720 x 576
	TV system	PAL
	Frame rate	25-30 frames/sec
	TPU cable length	Approx. 600cm
	Dimensions	131mm x 100mm x 25.6mm
Weight	0.28KG	